



## The Most Cost Effective Solution!

Having cheap and customized signs promptly is certainly possible. Try Bobcat now. You will experience the joy of creating ideal signs at affordable costs.



- 🐾 Tri-port connectivity
- 🐾 Up to 60 centimeters per second of cutting speed
- 🐾 Up to 300 grams of cutting force
- 🐾 Multi-function
- 🐾 Guaranteed 3 meter tracking



Tri-Port connectivity



Cut and Plot in one machine



• Public Sign



• Office sign



• School Sign



• Store Sign



• Personalized Sign



• Application

| Model Name/No.                | BI-30                                              | BI-60               |
|-------------------------------|----------------------------------------------------|---------------------|
| Max. Cutting Width            | 300mm(11.81in)                                     | 590mm(23.23in)      |
| Max. Media Loading Width      | 459mm(18.07in)                                     | 719mm(28.3in)       |
| Min. Media Loading Width      | 52mm(2.05in)                                       | 50mm(1.97in)        |
| Acceptable Material Thickness | 0.8mm (0.03 in)                                    |                     |
| Number of Pinch Rollers       | 2                                                  |                     |
| Motor                         | DC Servo Control                                   |                     |
| Cutting Force                 | 0~300 g                                            |                     |
| Max. Cutting Speed            | Up to 600 mm /sec (23.62 ips)                      |                     |
| Memory                        | 16MB ( 4MB in buffer )                             |                     |
| Interfaces                    | USB 1.1 & Parallel (Centronics) & Serial (RS-232C) |                     |
| Commands                      | HP-GL, HP-GL/2                                     |                     |
| Control Panel                 | 10 Control Keys , 6 LEDs                           |                     |
| Dimension (HxWxD)             | 230x620x255mm                                      | 220x 879x258mm      |
|                               | 9.06 x24.4x10.04in                                 | 8.67 x34.61x10.16in |
| Net Weight                    | 10.6kg/23.32lb                                     | 11.2kg / 24.7lb     |
| Power Supply                  | AC 100-240V, 50~60 Hz (auto switching)             |                     |

※This specification is subject to change without prior notice.