



Jaguar IV

CUTTING PLOTTER

Series Models :
J4-61, J4-101S, J4-132S & J4-183S

The Revolutionary Generation
with Advanced AAS II Contour Cutting System



FEATURES

- * DC servo motor technology
- * Dual-port interface connectivity
- * Up to 600 grams of cutting force
- * Up to 60 inches per second of cutting speed
- * Up to 0.8mm (0.03 in) media thickness
- * Guaranteed 10 meter tracking
- * User-friendly & multi-language control panel
- * Ingenious media basket

Enhanced **AAS II** Contour Cutting System

The Jaguar IV series features a standard Automatic-Aligning System (AASII) to guarantee precise contour cutting by detecting the registration marks on digitally produced images.

The significant functions include:



1st-mark auto-detection



4-point positioning



Segmental Positioning



Multiple copy

User-Friendly Control Panel

The easy-to-use and multi-language control panel can remarkably simplify complex tasks. Available in 8 languages, the powerful control panel for the Jaguar IV series provides various functional settings to meet users' needs.

Efficient Throughput

At up to 60 inches per second of cutting speed, Jaguar IV's cutting rate simply outperforms the competition.

Intelligent Unroll Media

Cutting long-length plots or repeating jobs have never been this easy! The unroll media function can elevate the output quality and the tracking capability by reserving a safe margin of media in advance.

Selective Pinch Roller

Positioning (Patented)

Each pinch roller can be positioned and operated individually, widening the Jaguar IV's range of applications.

Innovative Tangential Mode

The tangential mode is able to perform clean cuttings, diminutive letterings and intricate graphics which yield smooth corners and sleek edges on thick materials.

Jaguar IV Specification

Model Number		J4-61	J4-101S	J4-132S	J4-183S
Operational Method		Roller-Type			
Max. Cutting Width		610 mm (24")	1016 mm (40")	1320 mm (52")	1830 mm (72")
Max. Cutting Length		50m (164 ft)			
Number of Pinch Rollers		3	4	6	
Max. Media Thickness		0.8 mm (0.03")			
Drive		DC Servo Control			
Max. Cutting Force		600 gram			
Max. Cutting Speed		1530 mm/sec (60 ips) (at 45° direction)			
Offset		0~1.0 mm (with an increase of 0.025 mm)			
Memory Buffer		4M			
Interfaces		USB 2.0 (Full Speed) and Serial (RS-232C)			
Type of Command		HP-GL, HP-GL/2			
Mechanical Resolution		0.006 mm			
Software Resolution		0.025 mm			
Distance Accuracy		± 0.254 mm or ± 0.1% of move, whichever is greater			
Repeatability		± Within 0.1 mm			
Curve & Arc Smoothing		Yes			
Configurable Origin		Yes			
Test Cut capability		Yes			
Tangential Mode		Yes			
Repeat		Yes			
Copy		Yes			
Pouncing		Yes			
Control Panel		LCD (20 digits x 2 lines), 14 Keys, 1 Power LED			
Diameter of Blade		2 mm			
Power Supply		AC 100-240V, 50~60 Hz (auto switching)			
Power Consumption		110 watts Max.			
Dimension		412 x 950 x 486 mm	1096 x 1450 x 651 mm	1111 x 1774 x 651 mm	1127 x 2170 x 756 mm
(H x W x D)		16.2" x 37.4" x 19.1"	43.1" x 57" x 25.6"	43.7" x 69.8" x 25.6"	44.4" x 85.4" x 29.8"
Net Weight		18 kg / 39.68 lb	41.5 kg / 91.49 lb	50 kg / 110.23 lb	63 kg / 138.6 lb
Stand		Optional	Standard		
Automatic-Aligning System		Completely Automatic contour cutting system for print to cut solution			
Media Basket		Optional			
Operation Environment	Temperature	15°C ~30° C / 60° F~86° F			
	Humidity	25% ~ 75%			

* Compatible with Windows 7 and above & MAC OS X 10.6 and above.

* The specification and data sheet may vary with different materials used. In order to obtain the best output quality, please maintain the machine regularly and properly.

* GCC reserves the right to change the specifications at any time without notice.

* The above listed specification values are effective only when operated with media certified by GCC.



www.GCCworld.com



GCC Headquarters	4F-1., No.236, Fude 2nd Rd., Xizhi Dist., New Taipei City 22151, Taiwan	886-2-6616-6692	Fax : 886-2-2694-6875
GCC China	No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China	86-512-5726-1515	Fax : 86-512-5726-1518
GCC Europe B.V.	Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands	31-10-458-9367	Fax : 31-10-451-9874
GCC America, Inc	323 Paseo Tesoro, Walnut, CA 91789, USA	1-909-718-0248	Fax : 1-909-718-0251
		US & Canada Only	Toll Free: 1-888-284-5211