



# GCC JC-240E PRINTER/CUTTER

GCC JC-240E Printer/Cutter allows users to apply on a wide variety of applications, such as wall Stickers, Vehicle Decoration, Sign, POS, POP, Label, Heat Transfer films... etc. Also, GCC JC-240E Printer/Cutter comes with the FlexiPRINT DX - GCC Edition RIP software which can easily complete the print and cut workflow with the user-friendly interface.

## Features:

- ◆ Printer / Cutter in one machine
- ◆ Media Thickness up to 10mm
- ◆ Print resolution of up to 1440 DPI with 6 colors available
- ◆ Maximum Throughput 3.48 m<sup>2</sup>/hr (37.2 ft<sup>2</sup>/hr)
- ◆ Auto Media Calibration (AMC™)
- ◆ Enhanced AAS II Contour Cutting System
- ◆ Professional cutting functions
- ◆ Bundled FlexiPRINT DX - GCC Edition RIP software

## ■ Heat Transfer



## ■ Wall Stickers



## ■ Vehicle Decoration



## ■ Sign / POS / POP



## ■ Label





FlexiPRINT- GCC Edition software, which is designed to raise your productivity with the ease-to-use interface, offers the simple Print & Cut workflow.

Benefits:

- Smart, Easy and Powerful
- One comprehensive solution, from design to production
- Contour Cutting performed quickly and easily
- Superior colors
- Boosts output with high-productivity features
- Complete Color Separation Tools

Model		JC - 240E
Media printing width	Roll	590mm (23.2 inch)
	Single sheet	600mm (23.6 inch)
Max. media width	Roll	610mm (24.0 inch)
	Single sheet	625mm (24.6 inch)
Print head adjustment		AMC™
Color Channel		8
Color - Standard		CMYK
Color - Option		Lc Lm
Media thickness		10mm (0.394 inch) *1
Roll weight		30kg (66.86 lbs)
Roll core diameter		Inside: 76.2 mm ( 3 inch )
Roll outer diameter		210mm ( 8.27 inch )
Ink type		Eco - solvent
Capacity		440 ml
Ink Package		Cartridge
Resolution		720 dpi (1440 dpi with Lc Lm - optional)
Automatic-Aligning System		Completely Automatic Contour Cutting System for print to cut solution
Max. Cutting Force		600 gram
Max. Cutting Speed		720 mm /sec (28.3 ips)
Distance Accuracy -When printing		Less than $\pm 0.3\%$ of distance traveled, or $\pm 0.3\text{mm}$ (0.01 inch), whichever is greater
Distance Accuracy -When cutting		Less than $\pm 0.4\%$ of distance traveled, or $\pm 0.3\text{mm}$ (0.01 inch), whichever is greater
Repeatability - When cutting		$\pm 0.1\text{mm}$ (0.0039 inch) or less
Alignment accuracy for printing and cutting		$\pm 0.5\text{mm}$ (0.0197 inch) or less
Alignment accuracy for printing and cutting when reloading media		Less than $\pm 0.5\%$ of distance traveled, or $\pm 3\text{mm}$ (0.1 inch), whichever is greater
Connectivity		Ethernet (10BASE - T/100BASE TX Automatic switch)
Voltage requirement		100 to 240 VAC 50/60HZ
Power consumption -Operating		110VAC (60HZ) (Max. 450W) 220VAC (50HZ) (Max. 470W)
Power consumption -Stand by		110VAC (60HZ) (Max. 60W ) 220VAC (50HZ) (Max. 70W )
(Temperature/Humidity)		22°C ~ 30°C (71.6°F ~ 86°F) / (40% ~ 60% humidity)
Dimension	1,618 (W) x 870 (D) x 1,301 (H) mm	
	63.7 (W) x 34.2 (D) x 51.2 (H) inch	
Weight		107 kg

\*1: Only available with the add-on flat table optional item.

\*Above specifications are subject to change without prior notice.



[www.GCCworld.com](http://www.GCCworld.com)



GCC Headquarters	4F-1., No.236, Fude 2nd RD., Xizhi Dist., New Taipei City 22151, Taiwan	886-2-6616-6692	Fax : 886-2-2694-6875
GCC China	No.1, Chen Feng Road, Yushan, Kunshan, Jiangsu 215300, China	86-512-5726-1515	Fax : 86-512-5726-1518
GCC Europe B.V.	Eglantierbaan 43-45, 2908 LV, Capelle a/d IJssel, The Netherlands	31-10-458-9367	Fax : 31-10-451-9874
GCC America, Inc	323 Paseo Tesoro, Walnut, CA 91789, USA	1-909-718-0248	Fax : 1-909-718-0251
		US & Canada Only	Toll Free: 1-888-284-5211